

LEVELS DISPLAYED:  
 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 ACC:  
 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32  
 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48  
 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63

DISCLAIMER  
 The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

# SUMMARY OF SMALL SIGNS

SM RD SGN ASSM TY XXXXX(X)(X-XXXX)

PLAN SHEET NO.	SIGN NO.	SIGN NOMENCLATURE	SIGN TEXT	SIGN DIMENSIONS	LEGEND SHEETING	BACKGROUND SHEETING	PLYWOOD TYPE A	ALUMINUM TYPE A	ALUMINUM TYPE G	Post Type FRP = Fiber glass TWT = Thin-Wall IOBWG = IO BWG S80 = Sch 80	Posts (lor 2)	Anchor Type UA = Univer-Conc UB = Univer-Bolt WA = Wedge-Conc SA = Slip-Conc SB = Slip-Bolt	Mounting Designation P = Prefab. "Plain" T = Prefab. "T" U = Prefab. "U" EXT or 2EXT = # of Ext. BM = Extruded Wind Beam WC = 1/2" #/ft <sup>2</sup> Wing Chan. EXAL = Extruded Alum. signs
4	1	R3-1	RIGHT TURN PROHIBITED	24X24						IO BWG	1	SA	P
	2	R1-1	STOP	30X30									
	3	R1-4	ALL WAY	18X6									
	4	R3-2	LEFT TURN PROHIBITED	24X24						IO BWG	1	SA	P
	5	R1-1	STOP	30X30									
	6	R1-4	ALL WAY	18X6									
	7	R11-2	ROAD CLOSED	48X30						IO BWG	1	SA	P
	8	R11-2	ROAD CLOSED	48X30						IO BWG	1	SA	P
	9	W3-1	STOP AHEAD	24X24						IO BWG	1	SA	P
	10	W3-1	STOP AHEAD	24X24						IO BWG	1	SA	P
	11	W2-1	↔	30X30						IO BWG	1	SA	P
	12	W16-8	JOHN KING BLVD	24X8						IO BWG	1	SA	P
	13	W2-1	↔	30X30						IO BWG	1	SA	P
	14	W16-8	JOHN KING BLVD	24X8									
	15	W2-1	↔ Access to Quail Run Rd and Hays Road Only	84X30						TWT	2	UA	P
	16	W2-1	↔ Access to Quail Run Rd and Hays Road Only	84X30						TWT	2	UA	P

**RECORD DRAWING**  
 This drawing is a compilation of the original sealed engineering drawing and modifications by addenda, change orders and information furnished by the contractor. Information shown that was provided by the contractor and others not associated with the design engineer cannot be verified for accuracy or completeness. Original sealed drawing is on file at the office of AECOM USA Group, Inc.  
 TBPE REG. NO. F-3082

△ REVISED OR ADDED 8/19/08

ALUMINUM SIGN BLANKS (TYPE A)  
 Square Ft. Min. Thickness  
 Less than 7.5 0.080"  
 7.5 to 15 0.100"  
 Greater than 15 0.125"

Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.

Reflective sheeting will be designated as:

Type C - High Specific Intensity  
 Type D - Non-fluorescent Prismatic

**SUMMARY OF SMALL SIGNS**

© TxDOT May 1987

DRW: MT	REVISIONS
ECR: BAS	11-93 7-02
DRW: FDN	8-95
CHK: CAL	1-02

STATE DISTRICT	FEDERAL REGION	FEDERAL AID PROJECT	SHEET
6			10A
COUNTY	CONTROL SECTION	JOB	HIGHWAY