



SANITARY SEWER CURVE DATA				
NO.	A	R	T	L
15	50° 23' 42"	148.78'	70.00'	130.86'
16	36° 50' 18"	365.62'	121.66'	234.88'
17	42° 37' 43"	249.96'	97.53'	185.98'

GENERAL NOTES

1. WATER METERS ARE SET TO THE CENTER OF THE LOT AND 1' BEHIND BACK OF CURB, EXCEPT WHERE NOTED OTHERWISE.
2. ALL SANITARY SEWER SERVICES ARE SET TO THE CENTER OF THE LOT, OR 10' OFF WATER SERVICE ON DOWNSTREAM SIDE, EXCEPT AS NOTED.
3. WHERE CURVE DATA STATIONING IS NOT CALLED OUT FOR THE C. OF THE SAN. SEW. IT IS UNDERSTOOD THAT THE "P.C." OR "P.T." OCCURS AT EITHER THE MANHOLE OR THE CLEAN-OUT.
4. WATER LINES TO BE WARPED TO 5' OFF BACK OF CURB AT STORM SEWER INLETS.
5. PROPOSED MANHOLES UNDER THIS CONTRACT TO BE STUBBED FOR FUTURE LINES.

AS BUILT

WATER & SANITARY SEWER PHASE SIX - MASTER PLAN

DESIGN: W.H.W. R.M.H. DRAWN: R.M.H. DATE: FEB. 1974 SCALE: 1"=40'

CHANDLERS LANDING
ROCKWALL, TEXAS

228-8153 HAROLD EVANS CONSULTING ENGINEER DALLAS