

TOTAL AREA=7.06AC, AREA DETAINED=3.05 AC.

1. VOLUME REQUIRED

FREQUENCY = 10 YEAR

PRESENT CONDITION
 Td = 20 DESIGN TIME
 C = 0.35
 I = 5.68 IN/HR
 Q = C**A = 6.06 CFS

PROPOSED CONDITION
 Td = 10 DESIGN TIME
 C = 0.90
 I = 7.19 IN/HR
 Q = C**A = 19.74 CFS

MAX. RELEASE RATE = PRESENT CONDITION-DIRECT DISCHARGE
 MAX. RELEASE RATE = 6.06 - 0.00 = 6.06 CFS

TIME	INTENSITY	DISCHARGE	INFLOW	OUTFLOW	STORAGE
10	7.19	19.74	11,841.93	3,638.04	8,203.89
15	6.35	17.43	15,687.68	4,547.95	11,140.13
20	5.68	15.59	18,709.92	5,457.06	13,252.86
25	5.14	14.11	21,163.95	6,366.57	14,797.38
30	4.70	12.90	23,222.70	7,276.08	15,946.62
35	4.33	11.89	24,860.29	8,185.59	16,774.70
40	4.01	11.01	26,417.88	9,095.10	17,322.78
45	3.73	10.24	27,644.90	10,004.61	17,640.29
50	3.50	9.61	28,622.50	10,914.12	17,708.38
55	3.29	9.03	29,802.47	11,823.63	17,878.84
60	3.10	8.51	30,634.20	12,733.14	17,901.06
70	2.78	7.63	32,050.62	14,552.16	17,498.46
80	2.63	6.94	33,335.28	16,371.18	16,964.10
90	2.32	6.37	34,389.36	18,190.20	16,199.16

FREQUENCY = 25 YEAR

PRESENT CONDITION
 Td = 20 DESIGN TIME
 C = 0.35
 I = 6.61 IN/HR
 Q = C**A = 7.06 CFS

PROPOSED CONDITION
 Td = 10 DESIGN TIME
 C = 0.90
 I = 8.22 IN/HR
 Q = C**A = 22.56 CFS

MAX. RELEASE RATE = PRESENT CONDITION-DIRECT DISCHARGE
 MAX. RELEASE RATE = 7.06 - 0.00 = 7.06 CFS

TIME	INTENSITY	DISCHARGE	INFLOW	OUTFLOW	STORAGE
10	8.22	22.56	13,638.34	4,233.71	9,404.64
15	7.35	20.12	18,108.77	5,292.13	12,816.63
20	6.61	18.14	21,773.34	6,350.56	15,422.78
25	6.01	16.90	24,746.18	7,408.98	17,337.19
30	5.50	15.10	27,175.50	8,467.41	18,708.09
35	5.07	13.92	29,226.02	9,525.84	19,700.18
40	4.69	12.87	30,897.72	10,584.26	20,313.46
45	4.37	12.00	32,388.26	11,642.69	20,745.57
50	4.08	11.20	33,598.80	12,701.12	20,897.69
55	3.83	10.51	34,694.06	13,759.54	20,934.51
60	3.60	9.88	35,675.20	14,817.97	20,757.23
70	3.21	8.61	37,008.09	16,934.82	20,073.27
80	2.90	7.96	38,210.40	19,051.67	18,158.73
90	2.64	7.25	39,132.72	21,168.53	17,964.20

FREQUENCY = 50 YEAR

PRESENT CONDITION
 Td = 20 DESIGN TIME
 C = 0.35
 I = 7.42 IN/HR
 Q = C**A = 7.92 CFS

PROPOSED CONDITION
 Td = 10 DESIGN TIME
 C = 0.90
 I = 9.01 IN/HR
 Q = C**A = 24.73 CFS

MAX. RELEASE RATE = PRESENT CONDITION-DIRECT DISCHARGE
 MAX. RELEASE RATE = 7.92 - 0.00 = 7.92 CFS

TIME	INTENSITY	DISCHARGE	INFLOW	OUTFLOW	STORAGE
10	9.01	24.73	14,839.47	4,752.51	10,086.96
15	8.16	22.40	20,159.28	5,940.64	14,218.64
20	7.42	20.37	24,441.48	7,128.77	17,312.72
25	6.77	18.58	27,875.48	8,316.89	19,558.58
30	6.20	17.02	30,534.20	9,505.02	21,029.18
35	5.70	15.65	32,857.65	10,693.15	22,164.50
40	5.25	14.41	34,587.00	11,881.28	22,705.73
45	4.86	13.34	36,019.89	13,069.40	22,950.49
50	4.50	12.35	37,057.50	14,257.53	22,799.97
55	4.19	11.50	37,955.12	15,445.66	22,509.46
60	3.90	10.71	38,539.80	16,633.79	21,906.02
70	3.41	9.36	39,313.89	19,010.04	20,303.85
80	3.00	8.24	39,528.00	21,386.30	18,141.71
90	2.66	7.30	39,429.18	23,762.55	15,666.63

FREQUENCY = 100 YEAR

PRESENT CONDITION
 Td = 20 DESIGN TIME
 C = 0.35
 I = 8.3 IN/HR
 Q = C**A = 8.86 CFS

PROPOSED CONDITION
 Td = 10 DESIGN TIME
 C = 0.90
 I = 9.8 IN/HR
 Q = C**A = 26.90 CFS

MAX. RELEASE RATE = PRESENT CONDITION-DIRECT DISCHARGE
 MAX. RELEASE RATE = 8.86 - 0.00 = 8.86 CFS

TIME	INTENSITY	DISCHARGE	INFLOW	OUTFLOW	STORAGE
10	9.80	26.90	16,140.60	5,316.15	10,824.45
15	9.00	24.71	22,234.50	6,645.19	15,589.31
20	8.30	22.78	27,340.20	7,974.23	19,365.98
25	7.50	20.59	30,881.25	9,303.28	21,577.98
30	7.10	19.48	33,981.10	10,632.30	23,448.80
35	6.40	17.57	36,892.80	11,961.34	24,931.46
40	5.90	16.20	38,869.20	13,290.38	25,578.83
45	5.40	14.82	40,022.10	14,619.41	25,402.69
50	5.00	13.73	41,175.00	15,948.45	25,226.55
55	4.80	13.18	43,480.80	17,277.49	26,203.31
60	4.50	12.35	44,469.00	18,606.53	25,862.48
70	4.00	10.98	46,118.00	21,294.60	24,823.40
80	3.70	10.16	48,751.20	23,922.68	24,828.53
90	3.40	9.33	50,398.20	26,550.75	23,817.45

2. VOLUME PROVIDED

SOUTHERN POND

ELEV	AREA	AVE. AREA	VOLUME	CUM. VOL.
537	7,378.14	6,718.39	6,718.39	26,239.15
536	6,056.64	5,438.81	5,438.81	19,520.76
535	4,858.97	4,319.05	4,319.05	14,061.96
534	3,779.12	3,299.12	3,299.12	9,742.81
533	2,819.11	2,399.02	2,399.02	6,443.80
532	1,978.92	1,694.85	1,694.85	4,044.78
531	1,410.77	1,183.45	1,183.45	2,349.94
530	956.13	781.51	781.51	1,166.49
529	566.89	404.98	404.98	404.98
528	243.06			

3. ALLOWABLE DISCHARGE(7.06-3.05=4.01 AC)

A. DETAINED = 6.06 CFS
 B. UN-DETAINED = C**A=0.9*7.19*4.01 = 25.95 CFS
 C. T O T A L = 32.00 CFS

A. DETAINED = 7.06 CFS
 B. UN-DETAINED = C**A=0.9*8.22*4.01 = 29.66 CFS
 C. T O T A L = 36.72 CFS

A. DETAINED = 7.92 CFS
 B. UN-DETAINED = C**A=0.9*9.01*4.01 = 32.52 CFS
 C. T O T A L = 40.44 CFS

A. DETAINED = 8.86 CFS
 B. UN-DETAINED = C**A=0.9*9.8*4.01 = 35.36 CFS
 C. T O T A L = 44.22 CFS

4. WATER SURFACE ELEVATION

19,520.76 - 14,061.96 CF = 536.00' -535.00'
 =5,458.80 CF = 1.00'
 =17,978.84 -14,061.96 = 3,916.88 CF = 0.72'
 W.S ELEV = 535.72'

26,239.15 - 19,520.76 CF = 537.00' -536.00'
 =6,718.39 CF = 1.00'
 =20,934.51 -19,520.76 = 1,413.75 CF = 0.21'
 W.S ELEV = 536.21'

26,239.15 - 19,520.76 CF = 537.00' -536.00'
 =6,718.39 CF = 1.00'
 =22,950.49 -19,520.76 = 3,429.73 CF = 0.51'
 W.S ELEV = 536.51'

26,239.15 - 19,520.76 CF = 537.00' -536.00'
 =6,718.39 CF = 1.00'
 =26,203.31 -19,520.76 = 6,682.55 CF = 0.99'
 W.S ELEV = 536.99'

REVISED TO CONFORM TO CONSTRUCTION RECORDS.
 DATE: 1/4/06

DETENTION POND # 1 (3.05 AC. CAPACITY)
 FLAGSTONE ESTATES
 CITY OF ROCKWALL
 ROCKWALL COUNTY, TEXAS

REVISION
 KEB
 CHECKED
 D.L.B.
 DRAWN
 9/04
 DATE
 014 32A DETENTION
 PROJECT
 32A
 OF

DOUPHRATE & ASSOCIATES, INC.
 ENGINEERING - PROJECT MANAGEMENT - SURVEYING
 2235 RIDGE RD., # 200 ROCKWALL, TEXAS 75087
 PHONE: (972)771-9004 FAX: (972)771-9005

THE SEAL APPEARING ON THIS DOCUMENT WAS AUTHORIZED BY ALL DOUPHRATE II TEXAS P.L.E. NO. 0102 ON 1/10/06