

 Skew Angle = 0° ⁽²⁾ At discharge end, chamfer may be $\frac{3}{4}$ ". (3) For 15° Skew ~ 1" For 30° Skew ~ 2" For 45° Skew ~ 3" (4) Quantities shown are for two Type PW-1 wings. Adjust concrete volume for Type PW-2 wings. To determine estimated quantities for two wings, multiply the tabulated values by Lw. Quantities shown do not include weight of Bars D. (5) Provide weepholes for Hw = 5'-0" and greater. Fill around weepholes with coarse gravel. 6 Extend Bars E₂ 1'-6" minimum into the wingwall footing. (7) Lap Bars M1 1'-6" minimum with Bars M2. (8) Bars G equally spaced at 8" maximum, place as shown. Provide at least two pair Bars G per wina. 9 0" min to 5'-0" max. Estimated_curb_heights are shown elsewhere in the plans. For structures with pedestrian rail, bicycle rail or curbs taller than 1'-0", refer to ECD standard. For structures with T6 bridge rail, refer to T6-CM standard. For structures with traffic rail, other than T6, refer to RAC standard. (10) For vehicle safety, the following requirements must be met: - For structures without bridge rail, curbs cannot project more than 3" above finished arade. - For structures with bridge rail, build curbs flush with finished grade. Reduce curb heights, if necessary, to meet the above requirements. No changes will be made in quantities and no additional compensation will be allowed for this work. (11) 1'-0" typical. 2'-0" typical when RAC standard is referenced elsewhere in the plans. (12) 3'-0" for Hw < 4'. (13) 6" for Hw < 4'. **GENERAL NOTES:** Designed in accordance with AASHTO LRFD Bridge Design Specifications. Provide Class "C" Concrete (f'c = 4200 psi, min 7.5 sack mix for pour in place) and Grade 60 reinforcing steel. Provide 1 $\frac{1}{4}$ " Min clear cover to reinforcing steel. Depth of toewalls for wingwalls and culverts may be reduced or eliminated when founded on solid rock, when directed by the Engineer. See BCS sheet for wingwall type and additional dimensions and information. The quantities for concrete and reinforcing steel resulting from the formulas given on this sheet are

for the Contractor's information only.

DESIGNER NOTES:

Type PW-1 can be used for all applications and must be used if railing is to be mounted to the wingwall. Type PW-2 can only be used for applications without a railing mounted to the wingwall.

Texas Department of Transportation					Pridge Division Standard
CONCRETE WINGWALLS					
WITH PARALLEL WINGS FOR BOX CULVERTS TYPES PW-1 AND PW-2					
PW					
FILE: pwstde01.dgn	DN: GAF	-	ск: САТ	DW: TXDO	Г ск: GAF
CTxDOT February 2010	CONT	SECT	JOB HI		HIGHWAY
REVISIONS			, ,		
11-10: Reinforcing Quantities. 01-12: PW-1 & PW-2.	DIST		COUNTY	, I	SHEET NO.

C8.1